



Wolf's Head Red Grease is a premium, multipurpose automotive/truck chassis and bearing lithium complex grease. Applicable in a variety of automotive and industrial uses requiring extreme pressure protection, oxidation, inhibition, water resistance, and anti-rust properties, including; disc brakes, wheel bearings, chassis, ball-joints, 5 wheels and others. It possesses excellent water resistant properties, corrosion resistant and rust preventative properties. This grease, offers outstanding extreme pressure and anti-weld protection making it ideal choice for off- highway heavy and construction equipment. Qualified under the NLGI GC-LB classification, Wolfs Head Red Grease is recommended for use in high-temperature, humidity, and water contamination applications such as mining, marine, and construction. This grease is also suitable for high speed bearings.

TYPICAL INSPECTION DATA

Wolf's Head Greases	Wolf's Head Red Grease
Color	Red
Texture	Smooth,Buttery
NLGI Grade	2
Thickener	Lithium Complex
Filler	1%
Dropping Point °C /°F	260/500
Timken OK Load Lbs. D-2509	50
Four Ball Weld Scar, mm D-2266	0.60
Four-Ball WeldPoint,kgf D-2596	
Four-Ball Load Wear Index	
Four-Ball last non-seizure Id.	250
45	
80	
Rust Corrosion Test, D-1743	Pass
Emcor Rust, IP220-mod,Distilled Water	0,0
Worked 60 Penetration, D-217	265-295
Penetration Consistency Change, Roll Stability, D-1831, mm/10	+/- 10 max
Wheel Bearing Leakage, D-4290, g loss	2.0
Oxidation Stability D-942, Pressure drop at 100 hrs, PSI	5
Copper Strip Corrosion, D-4048	1b
Oil Separation, D-1742, % loss	2.5
Water Spray Resistance, D-4049, % Spray-off	12
Water Washout, D-1264, wt% loss at 79°C(175°F).	4.5
Base Oil Characteristics	
Viscosities D-445:	
@ 100C, cSt.	13.50 - 16.50
@40C, cSt.	140 - 180
Viscosity Index	90

PERFORMANCE APPLICATION CHART

Applications	Wolf's Head
Red Grease	
CV joints	P
Chassis (auto)	A
Chassis (truck)	A
Conveyor Belts	A
Drum and Shoe Bearing	P
EP (extreme pressure)	A
Extreme Temperature	P
5TH Wheel	P
General Purpose	P
High Impact Environment	A
High Water Environment	P
Off-Road SUV/Utility	P
Off-Road Heavy Duty	A
Outboard/Marine	P
Table & RockNeck Bearings	A
Trunion Bearings	P
Wheel Bearing (auto/truck)	P
* P = preferred A= Applicable	



Product Description	Product Code	Pack Desc.	UPC Code - Each	UPC Code - Case
WOLF'S HEAD 100% SYN 0W-20	836-85657-36	4/1 GLP	824686856573	824686957775
WOLF'S HEAD 100% SYN 0W-20	836-85656-56	12/1 QTRT	824686856566	824686957607
WOLF'S HEAD 100% SYN 5W-20	836-95646-56	12/1 QTRT	824686956464	824686955054
WOLF'S HEAD 100% SYN 5W-20	836-95643-05	55 GL DR STL	824686956433	824686956433
WOLF'S HEAD 100% SYN 5W-30	836-95666-56	12/1 QTRT	824686956662	824686955061
WOLF'S HEAD 100% SYN 5W-30	836-95663-05	55 GL DR STL	824686956631	824686956631
WOLF'S HEAD 100% SYN 5W-40	836-85696-56	12/1 QTRT	824686856962	824686957621
WOLF'S HEAD ATF +4 FULL SYN	836-82883-05	55 GL DR STL	824686828839	824686828839
WOLF'S HEAD DEXRON VI SYN ATF	836-92876-56	12/1 QTRT	824686928768	824686954910
WOLF'S HEAD DEXRON VI SYN ATF	836-92873-05	55 GL DR STL	824686928737	824686928737
WOLF'S HEAD DOT 3 BRAKE OIL	836-85031-92	12/12 OZ	824686850311	824686955078
WOLF'S HEAD DX III-H/M ATF	836-92834-25	5 GLP	824686928348	824686928348
WOLF'S HEAD DX III-H/M ATF	836-92836-56	12/1 QTRT	824686928362	824686954545
WOLF'S HEAD DX III-H/M ATF	836-92833-05	55 GL DR STL	824686928331	824686928331
WOLF'S HEAD EX-D SYN BLD 15W40	836-99104-25	5 GLP	824686991045	824686991045
WOLF'S HEAD EX-D SYN BLD 15W40	836-99107-36	4/1 GLP	824686991076	824686954453
WOLF'S HEAD EX-D SYN BLD 15W40	836-99106-56	12/1 QTRT	824686991069	824686954538
WOLF'S HEAD EX-D SYN BLD 15W40	836-99103-05	55 GL DR STL	824686991038	824686991038
WOLF'S HEAD EXTREME-DUTY 10	836-81913-05	55 GL DR STL	824686819134	824686819134
WOLF'S HEAD EXTREME-DUTY 30	836-81934-25	5 GLP	824686819349	824686819349
WOLF'S HEAD EXTREME-DUTY 30	836-81933-05	55 GL DR STL	824686819332	824686819332
WOLF'S HEAD EXTREME-DUTY 40	836-81944-25	5 GLP	824686819448	824686819448
WOLF'S HEAD EXTREME-DUTY 40	836-81943-05	55 GL DR STL	824686819431	824686819431
WOLF'S HEAD HDX GL-5 80W90	836-93124-25	5 GLP	824686931249	824686931249
WOLF'S HEAD HDX GL-5 80W90	836-93126-56	12/1 QTRT	824686931263	824686954552
WOLF'S HEAD HDX GL-5 80W90	836-93120-16	16 GL DR	824686931201	824686931201
WOLF'S HEAD HDX GL-5 80W90	836-93123-05	55 GL DR STL	824686931232	824686931232
WOLF'S HEAD HDX GL-5 85W140	836-93154-25	5 GLP	824686931546	824686931546
WOLF'S HEAD HDX GL-5 85W140	836-93156-56	12/1 QTRT	824686931560	824686954569
WOLF'S HEAD HDX GL-5 85W140	836-93150-16	16 GL DR	824686931508	824686931508
WOLF'S HEAD HDX GL-5 85W140	836-93153-05	55 GL DR STL	824686931539	824686931539
WOLF'S HEAD HEAVY-DUTY 30	836-81036-56	12/1 QTRT	824686810360	824686954477
WOLF'S HEAD HEAVY-DUTY 30	836-81033-05	55 GL DR STL	824686810339	824686810339
WOLF'S HEAD HEAVY-DUTY 40	836-81046-56	12/1 QTRT	824686810469	824686954484
WOLF'S HEAD HEAVY-DUTY 40	836-81043-05	55 GL DR STL	824686810438	824686810438
WOLF'S HEAD HYD/COMP OIL ND 30	836-80536-56	12/1 QTRT	824686805366	824686954460
WOLF'S HEAD HYD/COMP OIL ND 30	836-80533-05	55 GL DR STL	824686805335	824686805335
WOLF'S HEAD OB & 2-CYC TC-W 3	836-82733-05	55 GL DR STL	824686827337	824686827337
WOLF'S HEAD POWER STEERING FLUID	836-85181-92	12/12 OZ	824686851813	824686955085
WOLF'S HEAD PREMIUM HYD AW 32	836-84124-25	5 GLP	824686841241	824686841241
WOLF'S HEAD PREMIUM HYD AW 32	836-84123-05	55 GL DR STL	824686841234	824686841234
WOLF'S HEAD PREMIUM HYD AW 46	836-84134-25	5 GLP	824686841340	824686841340
WOLF'S HEAD PREMIUM HYD AW 46	836-84133-05	55 GL DR STL	824686841333	824686841333
WOLF'S HEAD PREMIUM HYD AW 68	836-84144-25	5 GLP	824686841449	824686841449
WOLF'S HEAD PREMIUM HYD AW 68	836-84143-05	55 GL DR STL	824686841432	824686841432
WOLF'S HEAD RED GREASE	836-88306-93	12/1 LB	824686883067	824686954620
WOLF'S HEAD RED GREASE	836-88301-91	50/14 OZ	824686883012	824686954613
WOLF'S HEAD SD SEMI SYN 5W20	836-91046-56	12/1 QTRT	824686910466	824686954699
WOLF'S HEAD SD SEMI SYN 5W20	836-91043-05	55 GL DR STL	824686910435	824686910435
WOLF'S HEAD SD SEMI SYN 5W30	836-91066-56	12/1 QTRT	824686910664	824686954491
WOLF'S HEAD SD SEMI SYN 5W30	836-91063-05	55 GL DR STL	824686910633	824686910633
WOLF'S HEAD SUPER DUTY 10W-40	836-91087-36	4/1 GLP	824686910879	824686956020
WOLF'S HEAD SUPER DUTY 20W-50	836-91097-36	4/1 GLP	824686910978	824686956129
WOLF'S HEAD SUPER DUTY SEMI-SYN 5W-30	836-91067-36	4/1 GLP	824686910671	824686957812
WOLF'S HEAD SUPER UNIV SYN ATF	836-92866-56	12/1 QTRT	824686928666	824686954576
WOLF'S HEAD SUPER UNIV SYN ATF	836-92863-05	55 GL DR STL	824686928638	824686928638
WOLF'S HEAD SUPER-DUTY 10W30	836-91076-56	12/1 QTRT	824686910763	824686954507
WOLF'S HEAD SUPER-DUTY 10W30	836-91073-05	55 GL DR STL	824686910732	824686910732
WOLF'S HEAD SUPER-DUTY 10W40	836-91086-56	12/1 QTRT	824686910862	824686954514
WOLF'S HEAD SUPER-DUTY 10W40	836-91083-05	55 GL DR STL	824686910831	824686910831
WOLF'S HEAD SUPER-DUTY 20W50	836-91096-56	12/1 QTRT	824686910961	824686954521
WOLF'S HEAD SUPER-DUTY 20W50	836-91093-05	55 GL DR STL	824686910930	824686910930
WOLF'S HEAD TRACTOR HT FLUID	836-83434-25	5 GLP	824686834342	824686834342
WOLF'S HEAD TRACTOR HT FLUID	836-83433-05	55 GL DR STL	824686834335	824686834335
WOLF'S HEAD UNIV SYN CVT FLUID	836-92883-05	55 GL DR STL	824686928836	824686928836

Some performance levels are limited by viscosity grades. Please consult the Wolf's Head Performance Application Chart, the Wolf's Head Inspection Data Table for the appropriate Wolf's Head product or contact your Wolf's Head District Manager for more complete information and recommendations. Consult your District Manager for specific pack sizes and product availability.

RUN WITH THE WOLF®

WOLF'S HEAD OIL COMPANY | 1601 McCloskey Blvd | Tampa, FL 33605 | (813) 248-1988 | www.wolfshead.com | info@wolfshead.com

RUN WITH THE WOLF®

WOLF'S HEAD OIL COMPANY | 1601 McCloskey Blvd | Tampa, FL 33605 | (813) 248-1988 | www.wolfshead.com | info@wolfshead.com