

# ZEN

## Efficient & Affordable

The new NeoECO Gold ZEN series feature high performance with an 80 PLUS Gold rating, achieving up to 92% efficiency and gives you savings unheard of from other power supplies.



### Specification

Model	NE500G ZEN	NE600G ZEN	NE700G ZEN
Type	ATX 12V 2,4	ATX 12V 2,4	ATX 12V 2,4
Dimension	140(L) x 150(W) x 86(H)	140(L) x 150(W) x 86(H)	140(L) x 150(W) x 86(H)
Warranty	5 years	5 years	5 years
Input Voltage	100-240 VAC	100-240 VAC	100-240 VAC
Input Current	6A-3A	8A-4A	10A-5A
Input Frequency Range	50Hz-60Hz	50Hz-60Hz	50Hz-60Hz
PFC	Active PFC	Active PFC	Active PFC
Power Good Signal	100-500ms	100-500ms	100-500ms
Efficiency	92% Typically	92% Typically	92% Typically
Protection	OCP/OVP/UVP/SCP/OPP/NLO	OCP/OVP/UVP/SCP/OPP/NLO	OCP/OVP/UVP/SCP/OPP/NLO
Output Capacity	500W	600W	700W
Operation Temperature	0~40°C	0~40°C	0~40°C
Regulatory	cTUVus/TUV/CB/RCM/CE/CCC/BSMI/FCC	cTUVus/TUV/CB/RCM/CE/CCC/BSMI/FCC/KC	cTUVus/TUV/CB/RCM/CE/CCC/BSMI/FCC/KC
Fan	120mm Silence Fan	120mm Silence Fan	120mm Silence Fan
Certifications	80 Plus Gold	80 Plus Gold	80 Plus Gold
Connector	1 x MB 24(20+4) Pin	1 x MB 24(20+4) Pin	1 x MB 24(20+4) Pin
	1 x 8(4+4) Pin EPS 12V	1 x 8(4+4) Pin EPS 12V	2 x 8(4+4) Pin EPS 12V
	2 x 8(6+2) Pin PCI-E	4 x 8(6+2) Pin PCI-E	4 x 8(6+2) Pin PCI-E
	6 x SATA	6 x SATA	6 x SATA
	2 x Molex	2 x Molex	2 x Molex