

CyberPower

P704URC1

ESSENTIAL SURGE PROTECTOR

Protect home and office computers, electronics, and home theater equipment

The CyberPower P704URC1 seven-outlet surge protector offers a high level of surge protection for common home and office electronics such as computers and peripherals, home theater equipment, and appliances. With 2000 joules of surge protection, the P704URC1 prevents power surges and power spikes caused by storms and electrical grid fluctuations from reaching and potentially harming your valuable electronic equipment. In addition to surge protection, the P704URC1 has two USB-A ports rated at 2.4 amps of shared output, which will charge USB enabled mobile device. The P704URC1 comes with seven standard, grounded power outlets and a 4-foot power cord with a low profile grounded plug, which fits tightly against walls for placement behind furniture.

Features of the P704URC1 include automatic shutdown, metal oxide varistor (MOV) technology, an EMI/RFI noise filter, keyhole mounting slots, and an impact-resistant casing. This surge suppressor comes with a one-year Limited Warranty and a Connected Equipment Guarantee.

TYPICAL APPLICATIONS

- Personal Computers
- Chargers
- Personal Electronics

FEATURES

- AC Outlets: 7
- AC Outlet Type: NEMA 5-15R
- Surge Protection: 2000 Joules
- USB-A Ports: 2
- USB-A Output: 2.4 A (shared)
- Cord Length: 4 ft.
- Plug Type: NEMA 5-15P
- Plug Style: Flat
- Electrical Rating: 125V / 15A / 60Hz
- Connected Equipment Guarantee: \$200,000
- Warranty: One-Year Limited Warranty

SPECIFICATIONS

INPUT	
Circuit Breaker	15 A
Cord Length	4 ft (1.2 m)
Input Plug Type	NEMA 5-15P
Maximum Input Current	15 A
Plug Style	45° Offset Right

OUTPUT	
Outlet Type	7 NEMA 5-15R
Outlets - Total	7
Output Voltage	125 VAC
Output Watts - Continuous	1,875 W
USB Charge Port	Yes
USB Charge Port Amperage	2.4 Amps (Shared)
USB Charge Port Quantity	2
USB Charge Port Type	2 Type A
USB Charge Port Voltage	5 VDC



P704URC1

ESSENTIAL SURGE PROTECTOR

SPECIFICATIONS - CONT

SURGE PROTECTION & FILTERING	
Attenuation	32 dB
Clamping Voltage	600V (H-N, H-G, N-G)
EMI/RFI Filtration	150 KHz 100 MHz Yes
Maximum Surge Current	60,000 A
Maximum Surge Current H-G	15,000 A
Maximum Surge Current H-N	30,000 A
Maximum Surge Current N-G	15,000 A
Maximum Surge Voltage	6,000 V
Response Time	<1 Nanosecond
Surge Suppression (Joules)	2,000 J
PHYSICAL	
Color	White
Form Factors Supported	Keyhole (Wall Mount or Under-counter Installation)
Material of Construction	Plastic
PHYSICAL DIMENSIONS	
Physical Dimensions - Width/Height/Depth (cm)	5.21 x 3.99 x 31.9 cm
Physical Dimensions - Width/Height/Depth (mm)	52 x 40 x 319 mm
Physical Dimensions - Width/Height/Depth (in.)	2.05 x 1.57 x 12.56 in.
Weight (kg)	0.41 kg
Weight (lbs.)	0.90 lbs.

SHIPPING DIMENSIONS	
Shipping Dimensions - Width/Height/Depth (cm)	10.8 x 37.47 x 4.45 cm
Shipping Dimensions - Width/Height/Depth (mm)	107.95 x 374.65 x 44.45 mm
Shipping Dimensions - Width/Height/Depth (in.)	4.25 x 14.75 x 1.75 in.
Shipping Weight (kg)	0.45 kg
Shipping Weight (lbs.)	1.0 lbs.
CERTIFICATIONS	
Environmental	RoHS Compliant
Safety	UL1363 UL1449 4th Edition UL1310 cUL FCC DOE VI
WARRANTY	
CEG Amount	\$200,000
Connected Equipment Guarantee	Lifetime
Product Warranty	One-Year Limited